

Racer

ELE400002



Item no. ELE400002-01E

General Product Information

Dimensions LxWxH	71x36x68 cm
Age group	2 - 5
Play capacity (users)	1
Colour options	



The Racer with its whimsical rodeo look attracts toddlers for a ride again and again. Apart from its appealing shapes, the Racer offers tactile variation with its rubber hand holds and smooth body. Tactile richness is a main motivator, especially in younger children. It supports their understanding of material characteristics such as weight, smoothness,

temperature and flexibility. The slightly sloped seat provides a seating destination that ensures hours, years and decades of fun. The soothing, rocking movement of the Racer trains the sense of balance and the spatial awareness. These are both crucial for body confidence, e.g. fall prevention. A well developed sense of balance is fundamental for

the ability to sit still and concentrate. The Racer offers children more than a mere fun ride.



Racer

ELE400002



The seat is made of recyclable PE and molded in one piece with a minimum 5mm wall thickness. PE has high impact resistance across a wide temperature span which ensures vandal resistance in all locations.

KOMPAN Springs are made of high quality spring steel according to EN10270. The springs are cleaned by phosphating before they are painted with an epoxy primer and a polyester powder coating as top finish. The springs are fixed by unique anti pinch fittings for maximum safety and long lifetime.

The springs are fixed by unique anti pinch fittings for maximum safety and long lifetime.



Handles are made with a molded PP insert and an outer layer of soft TPV rubber. The handles are attached to the pipe with a galvanized steel inlay to ensure strength and durability.



The steel surfaces are hot-dip galvanized inside and outside with lead-free zinc. The galvanization has excellent corrosion resistance in outside environments and requires minimal maintenance.



KOMPAN GreenLine versions are designed with the most environmentally friendly materials with the lowest possible CO2e emission factor such as EcoCore™ panels of 100% post-consumer recycled ocean waste.

Item no. ELE400002-01E

Installation Information

Max. fall height	43 cm
Safety surfacing area	14,2 m ²
Total installation time	1,4
Excavation volume	0,19 m ³
Concrete volume	0,00 m ³
Footing depth (standard)	45 cm
Shipment weight	37 kg
Anchoring options	In-ground ✓ Surface ✓

Warranty Information

Hollow PE Parts	10 years
Springs	5 years
Hot dip galvanized steel	Lifetime
Handle	10 years
Spare parts guaranteed	10 years






Cradle to Gate A1-A3	Total CO ₂ emission	CO ₂ e/kg	Recycled materials
	kg CO ₂ e	kg CO ₂ e/kg	%
ELE400002-01E	81,20	2,53	37,00
ELE400002-01DT	79,60	2,48	40,90

The overall framework applied for these factors is the Environmental Product Declaration (EPD), which quantifies "environmental information on the life cycle of a product and enable comparisons between products fulfilling the same function" (ISO, 2006). This follows the structure and applies a Life-Cycle Assessment approach to the entire Product stage from raw material through manufacturing (A1-A3))

Kompan A/S
 C.F. Tietgens Boulevard 32C
 DK-5220 Odense SØ
 Denmark



Validation of CO₂ calculation of: Freestanding play equipment



Data version no. 2021-09-27

The CO₂ calculation and data are in compliance with the principles of a carbon footprint impact according to the GHG protocol (Greenhouse Gas Protocol), Scope 3, cradle to gate related to all individual components in the product category: "Freestanding play equipment" represented by item no.: GXY916012-3417.

(Scope 3 emissions include emission sources in the upstream and downstream value chain).

Date: 15. October 2021 | Valid until: 15. October 2023

Validated by:

Bente Hviid, Senior Consultant

Peter Bendtsen, Senior Consultant

Validation based on report: Validation of CO₂ calculation of 8 categories of Kompan product line, version 1.0, prepared by: Bureau Veritas HSE, Denmark: Bente Hviid and Peter Bendtsen.

Publication date: 15. October 2021

By Bureau Veritas HSE
 www.bureauveritas.dk
 +45 7731 1000




Racer


ELE400002

* Max fall height | ** Total height | *** Safety surfacing area

* Max fall height | ** Total height



ELE400002
*1'-5" / 43cm
**2'-3" / 68cm
***152.8ft² / 14.2m²



[Click to see TOP VIEW](#)

[Click to see SIDE VIEW](#)